

6695-C

FROZEN BEVERAGE FREEZER

Two flavor, Countertop, Gravity feed









Powerful & Versatile

High capacity two flavor counter model for frozen beverage and milkshakes

Fast Freeze Down

Patented high efficiency heat exchanger allows fast freeze down with low energy consumption

Simple Control, Easy Operation

Simple and intuitive control system makes operation and viscosity adjustment easy, swift and more precise

Low Mix Indicator

Light turns "ON" at low mix to alert operator to add mix

See-through Dispensing Door

Clear dispensing door design makes product more attractive and serves as great marketing tool

Standby & Indicator

Maintains product temperature in both mix hopper and freezing cylinder below 4.4°C (40°F) overnight; Indicator lights up during Standby

Higher capacity solution with greater flexibility to serve larger crowds alcoholic & non-alcoholic frozen drinks including milkshakes

Hopper Agitators

Maintain product consistency and prevent product separation

Self-closing Dispensing Valve

Automatically prevents product overflow after dispense

Safety Protections

- High pressure switch to prevent compressor overheating
- $\bullet \ \, \text{Thermal overload to protect from motor overheating}$

Light Box (Optional)

- Illuminates flavor cards to attract more business
- · Changes color to indicate Low Mix and Standby

One-hand Operated Spinner (Optional)


- Adds ability to blend and offer more variaties of treats
- Allows for multi-tasking one-hand operation that helps increase productivity and reduce serving time






6695-C

FROZEN BEVERAGE FREEZER





SPECIFICATIONS

Flavors	2
Freezing Cylinders	2 x 6.9L / 7.3qt
Mix Hoppers	2 x 12L / 12.7qt
Output Capacity (250ml)	320 serves/hr
Clearance Requirements	152mm/6" on right

Weight	Kg/lb
Net	220 / 489
Shipping	235 / 522
Volume	0.51 CBM / 17.84 CBF

Dimensions	Net (mm/in)	Shipping (mm/in)
Width	532/20.9	570 / 22.4
Depth	652 / 25.7	800 / 31.5
Height	972 / 38.3	1110 / 43.7

Electrical	MFS	MCA	Power(kW)
220-240/50/1	20	15	2.4
208-230/60/1	20	17	2.7

• Above specifications are subject to change without notice

FEATURES	
Control Systems	Two, Mechanical
Refrigerated Hoppers	
Hopper Agitators	\checkmark
Standby Mode	
Auto Closing Dispensing Valves	\checkmark
Low Mix Indicator Light	
Low Mix Indicator Alarm	\checkmark
Standby Mode	
Standby Indicator Light	\checkmark
High Pressure Protection	
Thermal Overload Protection	$\overline{\mathbf{v}}$

AVAILABLE OPTIONS	
Top Air Discharge Chute	\checkmark
Spinner	
Light Box	\checkmark